

- SS7 Over IP Signalling -

The **IPTube•SS7•SIG•V35** transports SS7 messages over IP networks. SS7 signaling network elements such as local and tandem switches, Mobile Switching Centers, Signal Transfer Points and Home Location Registers that are interconnected to remote network elements by **IPTube•SS7•SIG•V35s** are able to transmit their signaling messages over cost effective and flexible IP networks.

The **IPTube•SS7•SIG•V35** is available as a DTE or a DCE industry standard V.35 interface. The DTE interface connects to the SS7 equipment's communication link through a T1 or E1 Multiplexor for connection to the SS7 DS0.



Reduced Transport Costs

Carriers significantly reduce SS7 transport costs by replacing expensive long-haul dedicated signaling links with very competitively priced IP connectivity between network elements. Service providers cut costs with SS7 Over IP by offloading data traffic from SS7 networks onto IP networks.

New Revenue Opportunities

The demand for data-centric services such as Short Message Service and Unified Messaging has created an opportunity for carriers to capitalize on new revenue generating opportunities. Cost-effective IP transport technology and service-rich SS7 applications enables carriers to quickly integrate enhanced services and capture new revenue.

Legacy Investment Protection

Establishing an SS7 network with **IPTube•SS7•SIGs** does not require expensive forklift replacements or costly software upgrades for existing end nodes.


Deployment Flexibility

Widely available commercial and private IP networks provides the SS7 network designer with competitive options for interconnecting the signaling points.

IPTube•SS7•SIG•V35

Industry Standard SS7 Framer

The **IPTube•SS7•SIG•V35** uses an industry standard SS7 Framer to receive and transmit SS7 messages. Minimal IP bandwidth is required to deliver SS7 since only the message data is encapsulated into IP packets.



Management of the **IPTube•SS7•SIG•V35** is accomplished with a Command Line Interface that is accessed through a Console or Telnet connection. Templates of the most common configuration provide for an Edit and Paste configuration.

Technical Specifications

LAN Network Interface:

- 10BaseT Ethernet

LAN Network Protocols Supported:

- IP, TCP, UDP, ICMP, BOOTP

SS7 Over IP Protocol:

- SS7 Frame UDP encapsuation

V.35 Interface:

- Standard DTE/DCE DB25 Female Adapter required
- DTR Controlled Transmission
- CD Reception Indicator

Regulatory:

- Safety - IEC60950
- EMC - CFR 47 Part 15 Sub Part B:2002
EN55022:1994+A1&A2
EN55024, ICES-003 1997
CISPR 22 Level A
- Telecom - Part68
- CE

Quality of Service Support:

- IP Type of Service (TOS) CLI configurable
- IANA Registered UDP Port 3175

TFTP Online Upgrade Capable (FLASH ROMs)

- IPTube is fully operational during upgrade

Management:

- Telnet support with Edit and Paste Template Files
- Console Port for Out of Band Management
- SNMP support (MIB I, MIB II)
- Remote configuration, monitoring, & reset

Power:


- 24VAC, 1.0A
- Optional 12-36 VDC 1.0A
- Optional -48V 0.25 Amp
- International Adapters Available

Dimensions:

- 9" (L) x 7.3" (W) x 1.50"

DC Back Panel


V.35 DTE/DCE Interface for connection to an SS7 Signalling Node



AC Back Panel

24 to 36 Volts DC Model
-36 to -72 Volts DC Model

V.35 DTE/DCE Interface for connection to an SS7 Signalling Node



Console Port Connector

- RJ 45 to DB 9 Male Adapter provided

Standard 10BaseT Ethernet interface

15-30 Volts AC